






适合线路板



结构外形(锁扣窗口)



以上结构外形(锁扣窗口)

7	8	9
标记 MARK	ECN编号/变更内容 ECN NO./DEFINITION	修改 REVISE
		日期 DATE
		核准 APPROVE

CKT	DIM A	DIM B	DIM C	DIM D
2	1.25	3.87	7.60	0.00
3	2.50	5.12	8.85	0.00
4	3.75	6.37	10.10	2.50
5	5.00	7.62	11.35	3.75
6	6.25	8.87	12.60	5.00
7	7.50	10.12	13.85	6.25
8	8.75	11.37	15.10	7.50
9	10.00	12.62	16.35	8.75
10	11.25	13.87	17.60	10.00
11	12.50	15.12	18.85	11.25
12	13.75	16.37	20.10	12.50
13	15.00	17.62	21.35	13.75
14	16.25	18.87	22.60	15.00
15	17.50	20.12	23.85	16.25
16	18.75	21.37	25.10	17.50

技术指标:

1. 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象。
 2. 温度范围: -40° C~85° C.
 3. 额定电压: 125V, AC/DC.
 4. 接触电阻: ≤0.02 Ω.
 5. 绝缘电阻: ≥100M Ω.
 6. 额定电流: 1.0A AC, DC
- 适用电线型号: a. AWG#28: 2.5A(per pin)
 b. AWG#30: 1.0A(per pin)
 c. AWG#32: 0.8A(per pin)

2	插针	铜	镀金	
1	基座	PA9T	米色	
序号	品名	材质	电镀/颜色	备注

	深圳市虹成电子有限公司		品名 TITLE	针座
			料号 PART NO	HCZZ0576-16
GENERAL TOLERANCES (UNLESS SPECIFIED)		比列 SCALE	1:1	
X.±0.30	X.±5°	单位 UNIT	MM	
.X±0.25	.X±3°	张数 PART NO	1 OF 1	制图 DRAW
.XX±0.20	.XX±1°	版本 REV	A	审核 CHECKED
		批准 APPROVE	夏操云	赵亮亮

