

## Serial ATA (SATA) Latching Signal Cable (7Pin/7Pin), 12-in. (30.48 cm)

MODEL NUMBER: **P940-12I**



### Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices
- Metal latches ensure secure connections
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design simplifies cable routing and installation and improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

## Specifications

| OVERVIEW                  |              |
|---------------------------|--------------|
| UPC Code                  | 037332184382 |
| Technology                | SATA/eSATA   |
| PHYSICAL                  |              |
| Color                     | Red          |
| Cable Jacket Color        | Red          |
| Cable Outer Diameter (OD) | 2.4/8.0mm    |
| Wire Gauge (AWG)          | 26           |
| Cable Length (ft.)        | 1            |
| Cable Length (m)          | 0.30         |

### Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

### Applications

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices

### System Requirements

- Serial ATA device
- Serial ATA controller

### Package Includes

- 12-in. Serial ATA (SATA) Latching Signal Cable  
7Pin/7Pin, Straight/Straight

|                                      |                            |
|--------------------------------------|----------------------------|
| Cable Length (in.)                   | 12                         |
| Cable Length (cm)                    | 30.48                      |
| Shipping Dimensions (hwd / in.)      | 0.12 x 4.00 x 6.00         |
| Shipping Dimensions (hwd / cm)       | 0.32 x 10.16 x 15.24       |
| Shipping Weight (lbs.)               | 0.04                       |
| Shipping Weight (kg)                 | 0.02                       |
| Unit Dimensions (hwd / in.)          | 0.125 x 4.000 x 6.000      |
| <b>CONNECTIONS</b>                   |                            |
| Side A - Connector 1                 | 7 PIN SATA STRAIGHT (MALE) |
| Side B - Connector 1                 | 7 PIN SATA STRAIGHT (MALE) |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                            |
| IP68 Rated                           | No                         |
| IP20 Rated                           | No                         |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                            |
| Product Compliance                   | RoHS                       |
| <b>WARRANTY &amp; SUPPORT</b>        |                            |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty  |