





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	LE3-910020	2009/01/06	Vicky	Modify the Wire Harness
D	LEN1350141	2013/05/08	Lu Di	Change Logo
E	LE31730067	2017/03/02	Ruru	Change Outer Mold Design


Conn.2





Conn.3



Back View



Conn.1



Pin Assignments Front View

Blue (24AWG) 藍	5	5	5
White (24AWG) 白	4	4	4
Black (22AWG) 黑	3	3	3
Red (22AWG) 紅	2	2	2
Green (24AWG) 綠	1	1	1
Wire Color	Conn.1	Conn.2	Conn.3

Pin Out

- Note:
- * $\varnothing$ Important Dimension
 - * Waterproof Rate: IP68
In 1 meter water within 24 hours
 - * Connector: PU, Black
 - * O- Ring: Viton, Green
 - * Screw Nut: Nylon+GF, Black
 - * Pin: Copper Alloy, Gold Plated
 - * Wire Harness: UL1061 24AWG, Green, White, Blue
 - * Wire Harness: UL1061 22AWG, Red, Black

UNIT:mm		TOLERANCE		TITLE		ITEM NO		DRAWN BY		DATE	
$\pm 0.5mm$				M12 Conn T Adaptor FFF Conn FFF Pin, 5Pin		PS-050505-FFF-TS001		Ruru		2017-03-02	
				SCALE 1:1		DWG NO PS-050505-FFF-TS001		CHECKED BY Rita		DATE 2017-03-02	
				REV. E		CUSTOMER ALTW		APPROVED BY Max		DATE 2017-03-02	
				WC-REV. A.1							
				$\varnothing$ Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.