



RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05

05XX-4BH806-F
1:AU 1U"
6:AU 30U"
T:TIN
N:NICKEL
S:Scrolls F:Flat

- NOTES:
- MATERIAL:
 - HOUSING:THERMOPLASTIC FLAMMABILITY RATING UL94-0
 - CONTACT:COPPERY ALLOY T=0.15MM
 - SHELL: COPPERY ALLOY T=0.25MM
 - FINISH:
 - CONTACT:
 - 1U"MIN,PLATED ON CONTACT AREA
 - G/F PLATING ON SOLDER TAIL AREA
 - 50~80U" NICKEL UNDERPLATING OVERALL
 - SHELL:
 - 80~120U" MATTER TIN PLAING ALL
 - 50~80U" NICKEL UNDERPLATING OVERALL
 - SPECIFICATION:
 - CURRENT RATING:0.5A(2.3.4CONTACT)/1.8A (1.5CONTACT)MAX.
 - VOLTAGE:30 VAC
 - TEMPERATURE RANGE:-30°C~85°C
 - CONTACT RESISTANCE:30 MILLIONHM MAX.
 - DIELECTRIC WITHSTANDING VOLTAGE;250VAC R.M.S
 - INSULATION RESISTNACE:100 MEGOHMS MIN

—		new		2015/5/3	A	瀚源
ECN BO.		DESCRIPTION.		DATE.	REV.	
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER	SCALT: 1/2		SCALE: 3:1
Mikey	Tom	Jerry	PART NAME	05XX-4BH806-F	UNLESS OTHERWISE SPECIFIED,TOLERANCE:	X. ±0.25
			MODEL NAME	05XX-4BH806-F		X.xx ±0.20
			3RD ANGLE PROJ	HanElectricity Co.,LTD		X.xx ±0.15
					ANGULAR	±3
					FILE.NO.	