



SECTION: A-A



SPECIFICATIONS

- Voltage rating: 250V AC/DC
- Current rating: 2A AC/DC
- Withstanding Voltage: 800V AC/minute
- Insulation resistance: 1,000MΩ min
- Temperature range: -40°C to +105 °C
- Contact resistance: 20mΩ max

WAFER

- Part No: CS-1261R-07
- Poles: 2-16
- Material: LCP UL94V-0
- Pin: Cooper needles (H65), Tin Plated (镀高温锡)
- Q' TY: 500 pcs/Tape&reel1
- Glow-wire 750°C temperature (灼热丝温度750°C)

POLE	PART NO	DIMENSION (mm)			PART NO	DIMENSION (mm)		
		A	B	C		Top entry type	A	B
2	CS-1261R-02	8.0	4.8	2.0	CS-1261R-10	24.0	20.8	18.0
3	CS-1261R-03	10.0	6.8	4.0	CS-1261R-11	26.0	22.8	20.0
4	CS-1261R-04	12.0	8.8	6.0	CS-1261R-12	28.0	24.8	22.0
5	CS-1261R-05	14.0	10.8	8.0	CS-1261R-13	30.0	26.8	24.0
6	CS-1261R-06	16.0	12.8	10.0	CS-1261R-14	32.0	28.8	26.0
7	CS-1261R-07	18.0	14.8	12.0	CS-1261R-15	34.0	30.8	28.0
8	CS-1261R-08	20.0	16.8	14.0	CS-1261R-16	36.0	32.8	30.0
9	CS-1261R-09	22.0	18.8	16.0				

ROHS 2.0

SOFT	WAFER	PART NO.	CS-1261R-07	X.	±0.50
VERSION	A/0	DESIGNER	李文畅	X.X	±0.30
FRAME	工程课	DRAW BY	李文畅	X.XX	±0.20
DRAWING NO.	CST-1261R	CHECK BY	YAO PEI ZHU	X.XXX	±0.10
DATE	2019-07-23	APPROVE	ZHOU ZHONG HU	X.XXXX	±0.05

MATERIAL	UNIT	mm	SHEET	1 OF 1
RIGIDITY <td>SCALE</td> <td>1:1 <td>REVISE</td> <td>REVISE DATE</td> </td>	SCALE	1:1 <td>REVISE</td> <td>REVISE DATE</td>	REVISE	REVISE DATE
PROJECTION	QUANTITY			



深圳市永豐盈電子有限公司
ShenZhenYongFengYing ELECTRONICS CO., LTD.

1	2	3

本圖紙知識產權及版權由永豐盈電子有限公司所有,未經書面許可不准擅自傳閱、複製和修改,本公司保留法律追究的權利.