



项目	规格
额定负荷	DC 12V 50mA
绝缘电阻	100MΩ min. 100v Dc
耐压强度	AC250V 50HZ 1min
电器寿命	20000次
环境温度	-25~70℃
相对湿度	(40℃) ≤95%
接触电阻	50mΩ max
行程	0.20±0.05mm
动作力	260gf±20gf

PAPT NO	TS1101S-X-X-X	
Operating Force	160 : 160gf ; 260 : 260gf	
Height	40 : 4.0mm	43 : 4.3mm
	45 : 4.5mm	50 : 5.0mm
	55 : 5.5mm	60 : 6.0mm
Color	B:Black W : White	

E	盖板	MA010-05	不锈铁带0.25	1	镀CT
D	按钮	MA010-04	PPA/G3白	1	
C	簧片	MA010-03	不锈钢覆银	1	
B	底座	MA010-02	PPA/G3白	1	
A	卡件	MA010-01	黄铜	1	镀银
序号	名称	物料号	材料	数量	备注

ECN BO.		DESCRIPTION.		DATE.	REV.	SCALE: 1/2	SCALE: 3:1
DESIGNED	CHECKED	APPROVAL	DRAWING NUMBER				
Mikey	Tom	Jerry	PART NAME	TS1101S-X-X-X	UNLESS OTHERWISE SPECIFIED, TOLERANCE:	X. ±0.25 X.x ±0.20 X.xx ±0.15 ANGULAIR ±3	FILE.NO.
			MODEL NAME	TS1101S-X-X-X			
			3RD ANGLE PROJ	HanElectricity Co.,LTD			

瀚源