

PRODUCT-DETAILS

SH203-C16

SH203-C16 Miniature Circuit Breaker - 3P - C - 16 A



SH203-C16	SH203-C16
2CDS213001R0164	2CDS213001R0164
4016779631334	4016779631334
SH203-C16 Miniature Circuit Breaker - 3P - C - 16 A	SH203-C16 Miniature Circuit Breaker - 3P - C - 16 A
<p>Compact Home SH200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 40 A). All MCBs of the product range SH200 comply with IEC/EN 60898-1, allowing the use for residential applications.</p>	

IEC/EN 60898-1	IEC/EN 60898-1
C	C
acc. to IEC 60898-1 400 V AC	acc. to IEC 60898-1 400 V AC
Maximum (Incl. Tolerance) 440 V AC Minimum 12 V AC	Maximum (Incl. Tolerance) 440 V AC Minimum 12 V AC
acc. to IEC/EN 60664-1 440 V	acc. to IEC/EN 60664-1 440 V
4 kV at 2000 m 5 kV at Sea Level 6.2 kV	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
50/60 Hz, 1 min: 2 kV	50/60 Hz, 1 min: 2 kV

□□□□□	AC
□□□□ (I n)	16 A
□□□□□	(AC) 6 kA (400 V AC) 6 kA
□□□□□□ (I nc)	(230 V) 6 kA (400 V) 6 kA
□□□□ (f)	50 / 60 Hz
□□□□	7.5 W at Rated Operating Conditions per Pole 2.5 W
□□□□	Arbitrary
□□□□□	ON / OFF
□□□□	3
□□□□□	20000 AC cycle
□□□□	20000 cycle
□□	3
□□□□	3
□□□□□	III
□□□□	2 N·m
□□□□□	Toggle
□□□□□□	Cage Terminal
□□□□□	I / O
□□□□□	Insulation Group II, Black, Sealable
□□□□	Insulation Group II, RAL 7035
□□□□□□□□	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
□□□□	any
□□□□□□	Pozidriv 2
Accessories Available	No
□□□□	Conductor 25 / 25 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 16 mm ² Rigid 0.75 ... 25 mm ² Stranded 0.75 ... 25 mm ²
□□□□□	acc. to DIN 43880 1
□□□□	Screw Terminals
<hr/>	
□□□□	
□□□□□	Operation -25 ... +55 °C Storage -40 ... +70 °C
□□□□□□□□	30 °C
□□□□	IP20 Enclosure with Cover IP40
□□□□	2
□□□□	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
□□□□□□ IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
□□□□□□ IEC 60068-2-27	25g 2 shocks 13 ms
RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS	2CDK400030D0201
REACH Declaration	9AKK107492A1906
□□□□	2CDK400030D0201

□□	
□□(□□□□□)	3
□□□□	52.5 mm
□□□□	85 mm
□□□□	69 mm
□□□□	0.375 kg
□□□□	0.125 kg
□□ (t ₂)	69 mm

□□□□	
□□□□	1 piece
1□□□□□	carton 1 piece
1□□□□ □	0.39 kg
E-Number (Finland)	3210169

□□□□□□□□□□	
□□□□	EN IEC
□□□□ - CE	2CDK400607D2703

Installation	
□□□□□□	2CDS207105P0001

Popular Downloads	
□□□□□□□□	2CSC400030D0202

□□	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
EPLAN□□□□	Electrical engineering / Protection devices / General
EPLAN□□□□	Circuit breaker / Triple circuit breaker / Triple circuit breaker 1_2_3_4_5_6
WEEE □□	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
e□	V11.0 : 27141901
IDEA □□□□□□ (IGCC)	4897 >> Miniature circuit breakers
□□□□□□	F

☐☐

☐☐☐☐☐

→ ☐☐☐☐☐

→ Miniature Circuit Breakers MCBs → ☐☐☐☐☐

